

TOTIME TM glodala za obradu čelika, sivog lijeva i inoxa

4 oštrice


Kut oštrice 35°

AlCrSiN presvlaka

Cilindrična izvedba



	Promjer oštrice D (mm)	Promjer stabla d (mm)	Rezni dio Lc (mm)	Ukupna dužina L (mm)	Broj oštrica Z
TOTIME55-010S-50-4F	1	6	3	50	4
TOTIME55-015S-50-4F	1,5	6	5	50	4
TOTIME55-020S-50-4F	2	6	6	50	4
TOTIME55-025S-50-4F	2,5	6	8	50	4
TOTIME55-030S-50-4F	3	6	10	50	4
TOTIME55-040S-50-4F	4	6	11	50	4
TOTIME55-040S-75-4F	4	6	13	75	4
TOTIME55-050S-50-4F	5	6	13	50	4
TOTIME55-060S-50-4F	6	6	18	50	4
TOTIME55-060-75-4F	6	6	20	75	4
TOTIME55-080S-60-4F	8	8	20	60	4
TOTIME55-080S-100-4F	8	8	25	100	4
TOTIME55-100S-75-4F	10	10	25	75	4
TOTIME55-100S-100-4F	10	10	30	100	4
TOTIME55-120S-75-4F	12	12	30	75	4
TOTIME55-120S-100-4F	12	12	35	100	4
TOTIME55-140S-100-4F	14	14	34	100	4
TOTIME55-160S-100-4F	16	16	45	100	4
TOTIME55-160S-150-4F	16	16	70	150	4
TOTIME55-180S-100-4F	18	18	45	150	4
TOTIME55-200S-100-4F	20	20	45	100	4



PREPORUČENI REŽIMI

$$ap \leq 1D$$

$$ae \leq 0.2D$$

P Vc - 180 m
Fz - 0.10 mm

M Vc - 120 m
Fz - 0.06 mm

K Vc - 160 m
Fz - 0.08 mm

TOTIME TM glodala šroperi za obradu čelika, sivog lijeva i inoxa

4 oštrice

Kut oštrice 35°

AlCrSiN presvlaka

Cilindrična izvedba



	Promjer oštrice D (mm)	Promjer stabla d (mm)	Rezni dio Lc (mm)	Ukupna dužina L (mm)	Broj oštrica Z
TOTIME55-040R-S-50-4F	4	4	12	50	4
TOTIME55-060R-S-50-4F	6	6	18	50	4
TOTIME55-080R-S-60-4F	8	8	20	60	4
TOTIME55-100R-S-75-4F	10	10	25	75	4
TOTIME55-120R-S-75-4F	12	12	30	75	4
TOTIME55-160R-S-100-4F	16	16	45	100	4
TOTIME55-200R-S-100-4F	20	20	45	100	4

PREPORUČENI REŽIMI

$$ap \leq 1D$$

$$ae \leq 0.2D$$

P Vc - 140 m
Fz - 0.09 mm

M Vc - 100 m
Fz - 0.05 mm

K Vc - 120 m
Fz - 0.07 mm