

OBAD Tools predstavlja TOTIME glodala za obradu aluminija

TOTIME45 glodala od Ø1 do Ø6 – **65 kn**

TOTIME45 glodala Ø8 L60 i Ø8 L100 – **95 kn**

TOTIME45 glodala Ø10 L75 i Ø8 L100 – **125 kn**

TOTIME45 glodala Ø12 L75 i Ø12 L100 – **155 kn**

TOTIME45 glodala Ø14 L100 i Ø16 L100 – **315 kn**

TOTIME45 glodala Ø16 L150, Ø18 L100 i Ø20 L100 – **425 kn**

TOTIME45 šroperi Ø4 i Ø6 – **95 kn**

TOTIME45 šroperi Ø8 – **145 kn**

TOTIME45 šroperi Ø10 – **175 kn**

TOTIME45 šroperi Ø12 – **235 kn**

TOTIME45 šroperi Ø16 – **535 kn**

PDV i dostava nisu uračunati.

Uz narudžbe iznad 2000 kn, glodača glava i paket pločica za obradu aluminija **GRATIS**.

Promocija vrijedi do vrijedi do 15.08.2020.

BESPLATNA DOSTAVA za narudžbe iznad 1000 kn





TOTIME TM glodala za obradu aluminija

3 oštrice

Kut oštrice 45°

Cilindrična izvedba



	Promjer oštrice D (mm)	Promjer stabla d (mm)	Rezni dio Lc (mm)	Ukupna dužina L (mm)	Broj oštrica Z
TOTIME45-010AL-50-3F	1	6	3	50	3
TOTIME45-015AL-50-3F	1,5	6	5	50	3
TOTIME45-020AL-50-3F	2	6	6	50	3
TOTIME45-025AL-50-3F	2,5	6	8	50	3
TOTIME45-030AL-50-3F	3	6	10	50	3
TOTIME45-040AL-50-3F	4	6	12	50	3
TOTIME45-040AL-75-3F	4	6	13	75	3
TOTIME45-050AL-50-3F	5	6	15	50	3
TOTIME45-060AL-50-3F	6	6	18	50	3
TOTIME45-060AL-75-3F	6	6	20	75	3
TOTIME45-080AL-60-3F	8	8	24	60	3
TOTIME45-080AL-100-3F	8	8	35	100	3
TOTIME45-100AL-75-3F	10	10	30	75	3
TOTIME45-100AL-100-3F	10	10	40	100	3
TOTIME45-120AL-75-3F	12	12	36	75	3
TOTIME45-120AL-100-3F	12	12	45	100	3
TOTIME45-140AL-100-3F	14	14	45	100	3
TOTIME45-160AL-100-3F	16	16	45	100	3
TOTIME45-160AL-150-3F	16	16	70	150	3
TOTIME45-180AL-100-3F	18	18	45	100	3
TOTIME45-200AL-100-3F	20	20	45	100	3

PREPORUČENI REŽIMI

ap ≤ 1.5D

ae ≤ 0.3D

N


**Vc - 350 m
Fz - 0.15 mm**

TOTIME TM glodala šroperi za obradu aluminija

3 oštrice

Kut oštrice 45°

Cilindrična izvedba



	Promjer oštrice D (mm)	Promjer stabla d (mm)	Rezni dio Lc (mm)	Ukupna dužina L (mm)	Broj oštrica Z
TOTIME55-040R-A-50-3F	4	4	12	50	3
TOTIME55-060R-A-50-3F	6	6	18	50	3
TOTIME55-080R-A-60-3F	8	8	20	60	3
TOTIME55-100R-A-75-3F	10	10	25	75	3
TOTIME55-120R-A-75-3F	12	12	30	75	3
TOTIME55-160R-A-100-3F	16	16	45	100	3
TOTIME55-200R-A-100-3F	20	20	45	100	3

PREPORUČENI REŽIMI

ap ≤ 1.5D

ae ≤ 0.2D

N

**Vc - 350 m
Fz - 0.12 mm**